

# MicroVol 1100

## LOW VOLUME AIR SAMPLER



**The MicroVol 1100 low volume air sampler provides a flexible sampling platform for PM<sub>10</sub>, PM<sub>2.5</sub> or TSP particulates and basic meteorological parameters.**

The MicroVol 1100 is suitable for both indoor and outdoor applications. The unit is microprocessor controlled and uses a mass flow sensor in conjunction with ambient temperature and pressure sensors to automatically maintain a constant volumetric flow rate.

### MEASUREMENTS CONSISTENT WITH\*

- PM<sub>10</sub> AS 3580.9.9 2017
- PM<sub>2.5</sub> AS 3580.9.10 2017

\* Keywood et al. (2000) CSIRO Atmospheric Research, 'Testing a low-cost aerosol sampler', Clean Air and Environmental Quality, Vol 34 No 4, pp. 38-42.

### INDOOR SAMPLING

- Low power consumption
- Quiet operation - ideal for indoor air quality studies
- Volumetric flow control automatically corrected to standard reference temperature
- Ultra-efficient, long life DC pump delivers flow rates of 1.0 to 4.5 L/min.

### OUTDOOR SAMPLING

- Wind direction and speed used to activate/de-activate sampler
- Fence line monitoring available with a network of samplers
- Built for all conditions - lightweight, rugged weatherproof construction
- Can operate via battery or solar powered sources (optional).

### ENHANCED COMMUNICATION

- RS232 output for data collection and remote communication
- Filter block and instrument error alarms available
- Total control of instrument remotely from PC
- Simple programming of sampling periods, including daily and weekly programs, with in built "1-in-X day" sampling capability.

### DIRECTIONAL SAMPLING

- Wind direction and speed used to activate/de-activate sampler
- External trigger (0 - 5 VDC) can be used for activating sampling program.

## SPECIFICATIONS

<b>Operation:</b>	Microprocessor controlled (internal data logging)
<b>Volumetric flow range/accuracy:</b>	1.0 - 4.5 L/m
<b>Flow accuracy:</b>	± 2 % of reading
<b>Flow repeatability:</b>	± 0.5 % of reading
<b>Temperature range accuracy:</b>	0 to 45 °C ± 1 °C
<b>Barometric pressure range:</b>	600 - 900 Torr ± 4 Torr
<b>Filter types:</b>	47 mm ringed circular filter
<b>Inlets available:</b>	PM <sub>10</sub> , TSP (standard), PM <sub>2.5</sub> (optional)
<b>Sampler dimensions:</b>	300 x 170 x 170
<b>Sampler weight:</b>	3.75kg
<b>Battery pack dimensions:</b>	185 x 170 x 170
<b>Battery pack weight:</b>	4.4 kg
<b>Battery pack life:</b>	Up to 40 hours sampling from fully charged battery pack
<b>Operating voltage:</b>	12 VDC
<b>Power consumption:</b>	2.5 - 3 watts depending on filter loading
<b>Standard accessories:</b>	<ul style="list-style-type: none"><li>• TSP/PM<sub>10</sub> size selective inlet</li><li>• Single 47 mm filter holder</li><li>• 100 - 240 AC to 12 VDC power converter</li><li>• MicroVol Downloader software</li><li>• RS232 cable</li></ul>

## COMMUNICATION & DATA LOGGING

### Number of readings

- 150 (averaging period is user selectable, e.g. 75 hrs of 30 min averages)

### External inputs

- 1 x wind direction sensor input (10 k potentiometer)
- 1 x wind speed sensor input (contact closure)
- 1 x spare contact closure input (e.g. tipping bucket rain gauge)

### Output

- RS232C

## OPTIONS

- Purpose built battery pack, or solar panel and battery pack
- Moisture elimination system
- Optional PM<sub>2.5</sub> size selective inlet adaptor
- Optional wind speed and direction sensor or tipping bucket rain gauge.



Acoem Australasia (Ecotech Pty Ltd)  
1492 Ferntree Gully Road Knoxfield VIC 3180 Melbourne Australia  
+61 3 9730 7800 email@acoem.com acoem.com.au

 **Ecotech**  
ACOEM Group